

- ◆ 恒压供水控制器
- ◆ 智能水泵变频器

不止创新 更懂服务 选炼尔 无忧愁



热线:13926482185 www.weierdianzi.com

S320系列供水专用变频器



功率范围: 0.75-7.5KW



功率范围: 0.75-7.5KW



S320系列变频器选型表

型号	功率	电压	型号	功率	电压	
液晶	液晶显示系列		数码显示系列			
S320S-CBP	0.75KW	220V	S320S-EBP	0.75KW	220V	
S320S-CBP	1.5KW	220V	S320S-EBP	1.5KW	220V	
S320S-CBP	2.2KW	220V	S320S-EBP	2.2KW	220V	
S320T-CBP	0.75KW	380V	S320T-EBP	0.75KW	380V	
S320T-CBP	1.5KW	380V	S320T-EBP	1.5KW	380V	
S320T-CBP	2.2KW	380V	S320T-EBP	2.2KW	380V	
S320T-CBP	4KW	380V	S320T-EBP	4KW	380V	
S320T-CBP	5.5KW	380V	S320T-EBP	5.5KW	380V	
S320T-CBP	7.5KW	380V	S320T-EBP	7.5KW	380V	

V510/S520系列智能变频器



功率范围: 0.75-55KW

V510/S520系列变频器选型表

变频器型号	电源容量 (KVA)	输入电流(A)	输出电流(A)	适配电机(KW)	
单相电源:220V (-15%~+20%),50/60Hz					
V510S/S520S-0.75G	1.5	8.2	4	0.75	
V510S/S520S-1.5G	3	14	7	1.5	
V510S/S520S-2.2G	4	23	9.6	2.2	
三相电源:380V (-15%~+20%),50/60Hz					
V510T/S520T-0.75G	1.5	3.4	2.1	0.75	
V510T/S520T-1.5G	3	5	3.8	1.5	
V510T/S520T-2.2G	4	5.8	5.1	2.2	
V510T/S520T-4G	5.9	10.5	9	4	
V510T/S520T-5.5G	8.9	14.6	13	5.5	
V510T/S520T-7.5G	11	20.5	17	7.5	
V510T/S520T-11G	17	16	25	11	
V510T/S520T-15G	21	35	32	15	
V510T/S520T-18.5G	24	38.5	37	18.5	
V510T/S520T-22G	30	46.5	45. 5	22	
V510T/S520T-30G	40	62	60	30	
V510T/S520T-37G	57	76	75	37	
V510T/S520T-45G	69	92	91	45	
V510T/S520T-55G	85	113	112	55	



S361系列智能变频器



功率范围: 0.75-22KW

S361系列变频器选型表

变频器型号	电源容量 (KVA)	输入电流(A)	输出电流(A)	适配电机(KW)		
单相电源:220V (-15%~+20%),50/60Hz						
S361S-2.2G-1/Y	2	17	17	2.2单相电容电机		
S361S-0.75G-1/N	1.5	8.2	4.00	0.75		
S361S-1.5G-1/N	3	14	7.00	1.5		
S361S-2.2G-1/N	4	23	9.60	2.2		
三相电源:380V (-15%~+20%),50/60Hz						
S361T-0.75G-1/N	1.5	3.4	2.1	0.75		
S361T-1.5G-1/N	3	5	3.8	1.5		
S361T-2.2G-1/N	4	5.8	5.1	2.2		
S361T-4G-1/N	5.9	10.5	9	3.7		
S361T-5.5G-1/N	8.9	14.6	13	5.5		
S361T-7.5G-1/N	11	20.5	17	7.5		
S361T-11G-1/N	17	16	25	11		
S361T-15G-1/N	21	35	32	15		
S361T-18.5G-1/N	24	38.5	37	18.5		
S361T-22G-1/N	30	46.5	45.5	22		

S326系列供水专用变频器



功率范围: 0.75-7.5KW

S326系列变频器选型表

变频器型号	电源容量 (KVA)	输入电流(A)	输出电流(A)	适配电机(KW)	
单相电源:220V(-15%~+20%),50/60Hz					
S326S-0.75KW	1.5	8.2	4	0.75	
S326S-1.5KW	3	14	7	1.5	
S326S-2.2KW	4	23	9	2.2	
三相电源: 380V (-15%~+20%) ,50/60Hz					
S326T-0.75KW	1.5	3.4	2.1	0.75	
S326T-1.5KW	3	5	3.8	1.5	
S326T-2.2KW	4	5.8	5.1	2.2	
S326T-4KW	5.9	10.5	9	3.7	
S326T-5.5KW	8.9	14.6	13	5.5	
S326T-7.5KW	11	20.5	17	7.5	



■ L系列恒压供水控制器



产品特点

结构紧凑,美观大方


可控制三台主泵

3.7寸中文液晶显示屏

适用于任何变频器

开孔: 85mm*163mm

■ S系列恒压供水控制器



产品特点

3.7寸中/英文液晶显示屏

4主泵1辅泵 (4+1)

RS485上位机集中控制

适用于任何变频器

可检测市网水压

开孔: 235mm*167mm

■ Q200系列分体式恒压供水控制器



产品特点

触摸屏可选7/10寸

接线方便、整体高档大方

画面生动、操作简单

显示内容丰富